

THE STORM CALCULATIONS ON THIS SHEET ARE UTILIZED FOR  
STORM SYSTEM CALCULATIONS ONLY. REFER TO STUDY  
SUBMITTED FOR ST. TERESA OF CALCUTTA CATHOLIC CHURCH  
FOR ANALYSIS POINT COMPARISON AND POND SIZING

St. Teresa of Calcutta																	
PROPOSED CONDITIONS DRAINAGE AREA COMPUTATIONS																	
Area Name	Runoff Coef. "C"	AREA "A" (ac.)	Total "CA"	Time of Concentration (min)	Ca 1	C*Ca 1	I1 (in/hr)	Q1 (cfs)	Ca 5	C*Ca 5	I5 (in/hr)	Q5 (cfs)	Ca 100	C*Ca 100	I100 (in/hr)	Q100 (cfs)	COMMENTS
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
A1	0.88	0.90	0.79	10.00	1.00	0.88	3.87	3.06	1.00	0.88	5.46	4.32	1.00	0.88	9.63	7.62	TO ALTA VISTA ROAD
A2	0.88	0.66	0.58	10.00	1.00	0.88	3.87	2.25	1.00	0.88	5.46	3.17	1.00	0.88	9.63	5.59	TO ALTA VISTA ROAD
B1	0.88	1.48	1.30	10.00	1.00	0.88	3.87	5.03	1.00	0.88	5.46	7.11	1.00	0.88	9.63	12.54	TO LANDSCAPE DRAIN
B2	0.88	0.34	0.30	10.00	1.00	0.88	3.87	1.16	1.00	0.88	5.46	1.63	1.00	0.88	9.63	2.88	TO LANDSCAPE DRAIN
B3	0.88	2.70	2.38	10.00	1.00	0.88	3.87	9.18	1.00	0.88	5.46	12.96	1.00	0.88	9.63	22.87	TO DETENTION POND

NOTES:  
1. RUNOFF COEFFICIENT FOR COMMERCIAL/INDUSTRIAL/HOUSE OF WORSHIP/SCHOOL FROM CITY OF FORT WORTH DESIGN CRITERIA MANUAL TABLE 3.5

Landscape Drain Sizing						
Area No.	No. of Inlets	Design Flow (cfs)	Design Head (ft.)	Inlet Size (in.)	Max Capacity (cfs)	Notes
B1	1	12.54	2.10	24	12.76	DOME GRATE INLET
B2	2	1.44	1.37	12	2.74	DOME GRATE INLET

NOTE: 1. INLETS SIZED USING 2012 NYLOPLAST GRATE INLET CAPACITY CHARTS  
2. AREAS WITH MULTIPLE INLETS HAVE BEEN SIZED FOR THE SAME DESIGN HEAD AND FLOW


Storm Year	Total Flow (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth(ft)	Outlet Control Depth(ft)	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
1-Year	15.31	15.31	672.07	1.13	2.12	0.65	0.66	2.42	2.42	1.27
5-Year	21.61	21.61	672.28	1.42	2.33	0.82	0.83	2.59	2.59	1.67
100-Year	38.12	38.12	673.47	2.06	3.52	1.21	1.22	3.00	3.67	2.54

NOTES:

1. CULVERT CAPACITY MODELED IN HY8, SEE CALCULATIONS ABOVE
2. RATIONAL FLOW FROM AREA B1-B3 WERE USED TO SIZE CULVERT

St. Teresa of Calcutta Storm Hydraulic Calculations																																													
Line No.	Station		Pipe Length	Drainage Area No.	Area	Total Area	C	Ca/Cf	Increment C*Cr*A	Total CA	Time of Concentration			I5	I (Design Below)	Q5	Q (Design Below)	Crown Overtop	Inlet Bypass	QPipe	Pipe Size			Manning s 'n'	Pipe Capacity	Sf	HGL		Head Loss Calculations										Entrance Control		Invert		Pipe Slope	T/C	Comments
	From	To									Inlet	Travel	Design								No.	Span	Dia/Height				D/S	U/S	V1	V2	V12/2g	V22/2g	Kj	KjV12/2g	Hk	Hwic	Control	Design HGL	From	To					
	ft	ft									min	min	min								in/hr	in/hr	in/hr				cfs	cfs	cfs	ft	ft	ft/s	ft/s	ft	ft	ft	ft	ft	ft	True/False	ft	ft			
1	2	3	4	5	6	7a	7b	8	9	10	11	13	14	15	16	17	18a	18b	19	20a	20b	20c	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40			
SD-A																																													
1	3+10.89	2+77.81	33.08	B1	1.48	1.48	0.88	1.00	1.30	1.30	10.00	0.08	10.00	5.46	9.63	7.11	12.54		12.54	1		18	0.012	15.52	1.21%	676.11	676.51	0.00	7.10	0.00	0.78	1.25	0.00	0.98	2.98	FALSE	677.49	674.20	673.59	1.86%	678.20	Inlet or Manhole at Beginning of Line			
2	2+77.81	2+11.30	66.51	B2	0.34	1.48	0.88	1.00	1.30	1.30	10.00	0.16	10.00	5.46	9.63	7.11	12.54		12.54	1	18	0.012	15.52	1.21%	675.03	675.84	7.10	7.10	0.78	0.78	0.35	0.27	0.27	0.00	FALSE	676.11	673.59	672.35	1.86%	680.48	Bend 45°				
3	2+11.30	1+00.00	111.30	B1	0.34	1.82	0.88	1.00	0.30	1.60	10.00	0.38	10.24	5.40	9.53	8.66	15.27		15.27	1	24	0.012	33.42	0.39%	674.50	674.93	7.10	4.86	0.78	0.37	0.75	0.29	0.10	0.00	FALSE	675.03	672.35	670.28	1.86%	680.48	45° Wye Connection or Cut-in				
SD-A1																																													
	1	4+13.37	4+02.09	11.28	B2	0.34	0.34	1.00	0.12	0.12	10.00	0.06	10.00	5.46	9.63	0.63	1.11		1.11	1	8	0.012	1.66	0.72%	678.51	678.59	0.00	3.18	0.00	0.16	1.25	0.00	0.20	0.84	TRUE	679.03	678.19	678.01	1.60%	681.53	Inlet or Manhole at Beginning of Line, Entrance Control				
	2	4+02.09	3+05.30	96.79		0.34	0.34		0.12	0.12	10.00	0.51	10.00	5.46	9.63	0.63	1.11		1.11	1	8	0.012	1.66	0.72%	677.30	678.41	3.18	3.18	0.16	0.16	0.35	0.06	0.10	0.00	FALSE	678.51	678.01	676.46	1.60%	681.64	Bend 45°				
	3	3+05.30	2+92.79	12.51		0.34	0.34		0.12	0.12	10.00	0.07	10.00	5.46	9.63	0.63	1.11		1.11	1	8	0.012	1.66	0.72%	676.76	676.86	3.18	3.18	0.16	0.16	0.50	0.08	0.10	0.84	TRUE	677.30	676.46	676.26	1.60%	681.40	Inlet on Main Line, Entrance Control				
	4	2+92.79	1+08.49	184.30		0.34	0.34		0.12	0.12	10.00	0.97	10.00	5.46	9.63	0.63	1.11		1.11	1	8	0.012	1.66	0.72%	675.19	676.66	3.18	3.18	0.16	0.16	0.35	0.06	0.10	0.00	FALSE	676.76	676.26	673.32	1.60%	682.50	Bend 45°				
	5	1+08.49	1+00.00	8.49		0.34	0.34		0.12	0.12	10.00	0.04	10.00	5.46	9.63	0.63	1.11		1.11	1	8	0.012	1.66	0.72%	675.03	675.09	3.18	3.18	0.16	0.16	0.35	0.06	0.10	0.00	FALSE	675.19	673.32	673.18	1.60%	679.35	Bend 45°				

PLOTTED BY: GABRIE SANCHEZ DATE: 2/16/2024 4:12 PM PATH: P:\3788-00-01\700 Land Development\703 Construction Documents\Design\Plot Sheets\DRAINAGE AREA MAP.dwg

ST. TERESA OF CALCUTTA CATHOLIC CHURCH FORT WORTH, TEXAS			
DRAINAGE CALCULATIONS			
 mma <small>civil engineering surveying landscape architecture planning</small>			
<small>ttxps registration number: f - 2759 ttxps registration/license number: 10088000 519 east border orlington, texas 76010 817-469-1671 fax: 817-274-8757 www.mmataxas.com</small>			
THIS DOCUMENT IS RELEASED FOR THE PURPOSES OF REVIEW UNDER THE AUTHORITY OF V. VALERIE ARRUDA, P.E., NO. 151600 ON 2/16/2024 AND IS NOT TO BE USED FOR CONSTRUCTION, BIDDING OR PERMIT PURPOSES.			
PROJECT NUMBER:		3788--00--01	
PROJECT MANAGER:		R. CRONIN	
DRAWN BY:		G. SANCHEZ	
CHECKED BY:		V. ARRUDA	
ISSUE DATE:		2/16/2024	
REV.	DATE	DESCRIP.	BY
SHEET CONTENT:			
DRAINAGE CALCULATIONS			
SHEET NO: C8.1			
COPYRIGHT © 2024 MMA, INC.			